

Disconnect the battery cable from the system board

How do you remove a battery from a computer?

Remove the three (M2x5) screws that secure the battery to the computer. Slightly lift the battery at an angle and slide the battery out of the computer chassis. Peel the plastic tape to release the battery cable from the battery. Unroute the battery cable from the routing guide in the battery and then disconnect from the connector on the battery.

How do I remove the touchpad cable from the system board?

Lift the connector latch and pull the pull-tab to disconnect the touchpad cable and keyboard-backlight cable from the connectors on the system board. 3 Remove the screws that secure the system board to the palm-rest assembly. 4 Turn the system board over and place it over the palm-rest assembly.

How do I replace a keyboard battery?

Slide both ends of the I/O-board cable into their connectors on the system board and I/O board, then close the latches to secure the cable. Adhere the I/O-board cable to the keyboard. Replace the battery. Replace the base cover.

How do I Disconnect a cable?

CAUTION: When you disconnect a cable, pull on its connector or on its pull-tab, not on the cable itself. Some cables have connectors with locking tabs; if you are disconnecting this type of cable, press in on the locking tabs before you disconnect the cable.

How do I replace a battery-status light cable?

Slide the battery-status light cable with microphones into the connector on the keyboard-controller board and close the latch to secure the cable. Adhere the tape that secures the battery-status light cable to the keyboard-controller board. Replace the battery. Replace the base cover.

How do you replace a laptop battery?

Connect the battery cable to its connector on the system board. Now, align the screw holes on the base cover with the screw holes on the palmrest and keyboard assembly and snap it into place. Replace any screws removed from the base cover and tighten the captive screws if applicable. Turn the system over.

Now, let's disconnect the battery cable from the system board. The placement of the battery connector may vary for your system. Once the battery is disconnected, turn the system back over and press the Power button to drain any remaining flea power. Remove the screws that secure the battery to the palmrest and keyboard assembly. Then, lift ...

If your computer is unable to enter Service Mode, disconnect the battery cable from the system board. Turn

Disconnect the battery cable from the system board

over your computer and open the display to access the power button. Press and hold the power button for five seconds to ...

then unplug the cable from the network device. 4. Disconnect all network cables from the computer. 5. Disconnect your computer and all attached devices from their electrical outlets. 6. Close the display and turn the computer upside-down on a flat work surface. NOTE: To avoid damaging the system board, you must remove the main battery before you

11. Connect the right speaker cable to the system board. 12. Connect the keyboard cable to the system board and close the latch to secure the cable. 13. Page 49: Installing The Led Board Steps 1. Open the latch and disconnect the ...

11 Record the cable routing and cable connections, and then disconnect all cables from the system board. See System board. 12 Replace the system board. Notes The numbers in the ...

Disconnect all network cables from the computer. Disconnect your computer and all attached devices from their electrical outlets. Close the display and turn the computer upside-down on a ...

Remove the base cover from the Chromebook. See the User Guide (Chromebook 3110 and Chromebook 3110 2-in-1) for instructions on removing the base cover. ...

Now, let's disconnect the battery cable from the system board. The placement of the battery connector may vary for your system. Once the battery is disconnected, turn the system back over and press the Power button to drain any remaining flea power. Remove the ...

4. Disconnect all network cables from the computer. 5. Disconnect your computer and all attached devices from their electrical outlets. 6. Close the display and turn the computer upside-down on a flat work surface. NOTE: To avoid damaging the system board, you must remove the main battery before you service the computer. 7. Remove the base ...

Remove the top cover (see Remove the top cover). Disconnect all the cables from the drive backplane. Locate the CMOS battery socket on the system board.

Coin-cell battery; M.2 storage drive; M.2 storage drive bracket; ... Record the cable routing and cable connections, and then disconnect all cables from the system board. See System board. 12. ... and then reconnect the cables to the new system board. See System board. 14. Reinstall the removed parts. To complete the replacement, see Completing ...

Web: <https://www.systemy-medyczne.pl>

Disconnect the battery cable from the system board